Safety Data Sheet

Issue Date: 27-Jul-2021 **Revision Date**: 28-Jul-2021 **Version** 1

1. IDENTIFICATION

Product identifier

Product Name CC-705

Other means of identification

SDS # WOHL-022

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Primer.

Details of the supplier of the safety data sheet

Supplier Address Wohl Coatings Co. 6161 Maple Ave. St. Louis, MO 63130

Emergency telephone number

Company Phone Number 314-725-3400

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Colored liquid according to product specification

Physical state Liquid

Odor Characteristic

Classification

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Signal Word

Danger

Hazard statements

Causes serious eye irritation
May cause genetic defects
May cause cancer
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor







Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof equipment

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Acetone	67-64-1	30-35
Calcium Carbonate	1317-65-3	10-15
Talc	14807-96-6	5-10
Stoddard solvent	8052-41-3	5-10
Aliphatic Hydrocarbon Solvent	64742-88-7	1-5
Iron(III) oxide	1309-37-1	1-5
Aromatic petroleum hydrocarbons	25551-13-7	1-5
Methanol	67-56-1	0.1-1
Xylene	1330-20-7	0.1-1
Quartz	14808-60-7	0.1-1
Ethylbenzene	100-41-4	0.1-1
Isopropylbenzene	98-82-8	0.1-1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

Description of first aid measures

General Advice If exposed or concerned: Get medical advice/attention.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash contaminated clothing before reuse.

Inhalation Remove to fresh air.

Ingestion Immediately call a poison center or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms May be harmful if swallowed. Causes serious eye irritation. May cause genetic defects. May

cause cancer. Causes damage to organs through prolonged or repeated exposure. May be

fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use CO2, dry chemical, or foam for extinction.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal PrecautionsUse personal protective equipment as required.

Environmental precautions

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands

read and understood. Use personal protective equipment as required. Wash face, hands

and any exposed skin thoroughly after handling. Do not breathe

dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Use explosion proof equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Store in a well-ventilated place. Keep cool.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
		sectors. (vacated) STEL: 1000 ppm	
Calcium Carbonate		TWA: 15 mg/m³ total dust	TWA: 10 mg/m³ total dust
1317-65-3	_	TWA: 13 mg/m total dust TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m total dust
1317-03-3		(vacated) TWA: 15 mg/m ³ total	TWA. 5 mg/m Tespirable dust
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
Talc	TWA: 2 mg/m³ particulate matter	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m ³
14807-96-6	containing no asbestos and <1%	respirable dust <1% Crystalline	TWA: 2 mg/m ³ containing no
	crystalline silica, respirable	silica, containing no Asbestos	Asbestos and <1% Quartz
	particulate matter	TWA: 20 mppcf if 1% Quartz or	respirable dust
		more;use Quartz limit	
Stoddard solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³
8052-41-3		TWA: 2900 mg/m ³	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m ³
		(vacated) TWA: 525 mg/m ³	
Iron(III) oxide	TWA: 5 mg/m³ respirable	TWA: 10 mg/m³ fume	IDLH: 2500 mg/m ³ Fe dust and
1309-37-1	particulate matter	TWA: 15 mg/m³ total dust	fume
		TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ fume	TWA: 5 mg/m³ Fe dust and fume
		and total dust Iron oxide	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction regulated	
		under Rouge	
Aromatic petroleum hydrocarbons	TWA: 25 ppm	(vacated) TWA: 25 ppm	-
25551-13-7		(vacated) TWA: 125 mg/m ³	
Methanol	STEL: 250 ppm	TWA: 200 ppm	IDLH: 6000 ppm
67-56-1	TWA: 200 ppm	TWA: 260 mg/m ³	TWA: 200 ppm
	S*	(vacated) TWA: 200 ppm	TWA: 260 mg/m ³
		(vacated) TWA: 260 mg/m ³	STEL: 250 ppm
		(vacated) STEL: 250 ppm	STEL: 325 mg/m ³
		(vacated) STEL: 325 mg/m ³	
V. J	OTEL . 450	(vacated) S*	
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³ (vacated) TWA: 100 ppm	
		(vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³	
		(vacated) TVVA. 435 flig/fli (vacated) STEL: 150 ppm	
		(vacated) STEL: 130 ppm (vacated) STEL: 655 mg/m ³	
		(1300100) 0.12E. 000 mg/m	
Oh amis - Lucius	ACOULT! V	OCUA DE	MOCHUELL
Chemical name Quartz	ACGIH TLV TWA: 0.025 mg/m³ respirable	OSHA PEL TWA: 50 µg/m³	NIOSH IDLH IDLH: 50 mg/m³ respirable dust
Quartz	T vvA. 0.025 mg/m respirable	i w.A. ου μg/iii	ום ווושלוו. שנו ווושלוו ווישלוו ווישלוו ווישלוו

14808-60-7	particulate matter	(vacated) TWA: 0.1 mg/m³ respirable dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	TWA: 0.05 mg/m³ respirable dust
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³
Isopropylbenzene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance Colored liquid according to product Odor Characteristic

specification

Color According to product specification Odor Threshold Not determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Flammability Limit in Air

Upper flammability or explosive Not determined

limits

Lower flammability or explosive Not determined

limits

Vapor PressureNot determinedVapor DensityNot determinedRelative DensityNot determinedWater SolubilityNot determinedSolubility in other solventsNot determinedPartition CoefficientNot determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Autoignition temperature Not determined

Decomposition temperature
Kinematic viscosity
Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Avoid contact with skin.

Inhalation Do not inhale.

Ingestion May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h	
Stoddard solvent 8052-41-3	-	> 3000 mg/kg (Rabbit)	-	
Aliphatic Hydrocarbon Solvent 64742-88-7	> 25 mL/kg(Rat)	> 4000 mg/kg (Rabbit)	> 13 mg/L (Rat) 4 h	
Iron(III) oxide 1309-37-1	> 10000 mg/kg (Rat)	-	-	
Bentone #34 68953-58-2	> 5000 mg/kg (Rat)	-	> 12.6 mg/L (Rat) 4 h	
Aromatic petroleum hydrocarbons 25551-13-7	= 8970 mg/kg (Rat)	-	-	
Methanol 67-56-1	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h	
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h	
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h	

Revision Date: 28-Jul-2021 WOHL-022 - CC-705

100-41-4			
Isopropylbenzene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye

irritation

Causes serious eye irritation.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

Chemical name	ACGIH	IARC	NTP	OSHA
Iron(III) oxide 1309-37-1		Group 3		
Xylene 1330-20-7		Group 3		
Ethylbenzene 100-41-4	А3	Group 2B		X
Isopropylbenzene 98-82-8		Group 2B	Reasonably Anticipated	Х

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Causes damage to organs through prolonged or repeated exposure. STOT - repeated exposure

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 3,476.80 mg/kg **Dermal LD50** 5,823.70 mg/kg 33,196.80 mg/L ATEmix (inhalation-dust/mist) 25.30 mg/L ATEmix (inhalation-vapor) 177.840 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Revision Date: 28-Jul-2021 WOHL-022 - CC-705

Chemical name	Algae/aquatic plants	Fish	Crustacea
Acetone		4.74 - 6.33: 96 h Oncorhynchus	10294 - 17704: 48 h Daphnia
67-64-1		mykiss mL/L LC50 6210 - 8120: 96 h Pimephales	magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia
		promelas mg/L LC50 static	magna mg/L EC50
		8300: 96 h Lepomis macrochirus	
		mg/L LC50	
Talc		100: 96 h Brachydanio rerio g/L	
14807-96-6 Aliphatic Hydrocarbon Solvent	450: 96 h Pseudokirchneriella	LC50 semi-static 800: 96 h Pimephales promelas	100: 48 h Daphnia magna mg/L
64742-88-7	subcapitata mg/L EC50	mg/L LC50 static	EC50
Iron(III) oxide		100000: 96 h Danio rerio mg/L LC50	
1309-37-1		static	
Aromatic petroleum hydrocarbons		7.72: 96 h Pimephales promelas	
25551-13-7 Methanol		mg/L LC50 flow-through 13500 - 17600: 96 h Lepomis	
67-56-1		macrochirus mg/L LC50 flow-	
07 00 1		through	
		18 - 20: 96 h Oncorhynchus mykiss	
		mL/L LC50 static	
		19500 - 20700: 96 h Oncorhynchus	
		mykiss mg/L LC50 flow-through 28200: 96 h Pimephales promelas	
		mg/L LC50 flow-through	
		100: 96 h Pimephales promelas	
		mg/L LC50 static	
Xylene		13.1 - 16.5: 96 h Lepomis	0.6: 48 h Gammarus lacustris mg/L
1330-20-7		macrochirus mg/L LC50 flow- through	LC50 3.82: 48 h water flea mg/L EC50
		13.5 - 17.3: 96 h Oncorhynchus	3.02. 40 11 Water fied flig/E E030
		mykiss mg/L LC50	
		2.661 - 4.093: 96 h Oncorhynchus	
		mykiss mg/L LC50 static	
		23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static	
		30.26 - 40.75: 96 h Poecilia	
		reticulata mg/L LC50 static	
		7.711 - 9.591: 96 h Lepomis	
		macrochirus mg/L LC50 static	
		13.4: 96 h Pimephales promelas mg/L LC50 flow-through	
		19: 96 h Lepomis macrochirus mg/L	
		LC50	
		780: 96 h Cyprinus carpio mg/L	
		LC50 semi-static	
		780: 96 h Cyprinus carpio mg/L LC50	
Ethylbenzene	1.7 - 7.6: 96 h Pseudokirchneriella	11.0 - 18.0: 96 h Oncorhynchus	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 static	mykiss mg/L LC50 static	EC50
	2.6 - 11.3: 72 h Pseudokirchneriella		
	subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella	promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales	
	subcapitata mg/L EC50	promelas mg/L LC50 static	
	438: 96 h Pseudokirchneriella	32: 96 h Lepomis macrochirus mg/L	
	subcapitata mg/L EC50	LC50 static	
		4.2: 96 h Oncorhynchus mykiss	
		mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L	
		LC50 static	
Isopropylbenzene	2.6: 72 h Pseudokirchneriella	6.04 - 6.61: 96 h Pimephales	7.9 - 14.1: 48 h Daphnia magna
98-82-8	subcapitata mg/L EC50	promelas mg/L LC50 flow-through	mg/L EC50 Static
		2.7: 96 h Oncorhynchus mykiss	0.6: 48 h Daphnia magna mg/L
		mg/L LC50 semi-static 4.8: 96 h Oncorhynchus mykiss	EC50
		mg/L LC50 flow-through	
		5.1: 96 h Poecilia reticulata mg/L	
		LC50 semi-static	

Persistence/Degradability
Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Methanol 67-56-1	-0.77
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.2
Isopropylbenzene 98-82-8	3.7

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1		Included in waste stream: F039		U002
Methanol 67-56-1		Included in waste stream: F039		U154
Xylene 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		
Isopropylbenzene 98-82-8				U055

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Methanol	Toxic
67-56-1	Ignitable
Xylene	Toxic
1330-20-7	Ignitable
Ethylbenzene	Toxic
100-41-4	Ignitable
Isopropylbenzene	Toxic
98-82-8	Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN1263 **UN/ID No Proper Shipping Name** Paint Hazard class 3 **Packing Group** Ш

IATA

UN number UN1263 **Proper Shipping Name** Paint Transport hazard class(es) 3 **Packing Group** Ш

IMDG

UN number UN1263 **Proper Shipping Name** Paint Transport hazard class(es) 3 **Packing Group** П

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
Acetone	X	ACTIVE	Х	X	Х	X	Х	X	Х
	_							1	
Calcium Carbonate	X	ACTIVE	X	X	Χ	Х	Х	X	X
Petroleum Resins	X	ACTIVE	X	X	Χ	X	X	X	X
Nepheline Syenite			Х			X			
Talc	Х	ACTIVE	Х	Х	Х	Х	Х	Х	Х
Stoddard solvent	X	ACTIVE	X	X		X	X	X	X
Aliphatic Hydrocarbon Solvent	Х	ACTIVE	Х	Х		Х	Х	Х	Х
Iron(III) oxide	X	ACTIVE	X	X	X	X	X	X	X
Chlorite				X		X	X	Х	
Bentone #34	Х	ACTIVE	Х	Х		Х	Х	Х	Х
Aromatic petroleum hydrocarbons	Х	ACTIVE	Х	Х	Х	Х	Х	Х	Х
Methanol	X	ACTIVE	X	X	X	X	X	X	X
Xylene	Χ	ACTIVE	X	X	Χ	X	X	X	X
Quartz	X	ACTIVE	X	X	X	X	X	X	X
Ethylbenzene	Х	ACTIVE	X	X	Χ	Х	X	Х	X
Lecithin	Х	ACTIVE	Х	X		X	Х	Х	
Isopropylbenzene	Χ	ACTIVE	Χ	X	Χ	Х	Χ	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

Revision Date: 28-Jul-2021 WOHL-022 - CC-705

CERCLA

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
Methanol	5000 lb		RQ 5000 lb final RQ
67-56-1			RQ 2270 kg final RQ
Xylene	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ
Isopropylbenzene	5000 lb		RQ 5000 lb final RQ
98-82-8			RQ 2270 kg final RQ

SARA 313

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methanol - 67-56-1	67-56-1	0.1-1	1.0
Xylene - 1330-20-7	1330-20-7	0.1-1	1.0
Ethylbenzene - 100-41-4	100-41-4	0.1-1	0.1
Isopropylbenzene - 98-82-8	98-82-8	0.1-1	0.1

CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb			Х
Ethylbenzene	1000 lb	X	X	X

US State Regulations

<u>California Proposition 65</u>
This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Methanol - 67-56-1	Developmental
Quartz - 14808-60-7	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Isopropylbenzene - 98-82-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	Х	X
Calcium Carbonate 1317-65-3	Χ	X	X
Talc 14807-96-6	Χ	X	X
Stoddard solvent 8052-41-3	X	X	X
Iron(III) oxide 1309-37-1	Х	Х	Х
Aromatic petroleum hydrocarbons 25551-13-7	Х	Х	Х
Methanol 67-56-1	Х	Х	Х
Xylene 1330-20-7	Х	X	X
Quartz 14808-60-7	Х	Х	Х
Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethylbenzene	X	X	X

100-41-4			
Isopropylbenzene	X	X	X
98-82-8			

16. OTHER INFORMATION

NFPA Health Hazards

Not determined
Health Hazards
Not determined

Flammability Not determined Flammability Not determined Instability
Not determined
Physical hazards
Not determined

Special Hazards Not determined Personal Protection Not determined

Issue Date:27-Jul-2021Revision Date:28-Jul-2021Revision Note:New format

Disclaimer

HMIS

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet